



- Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption E_b >10 %
- 2. Intended use(s)

For internal wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

- 4. System(s) of assessment and verification of constancy of performance (AVCP)

 Systems 4
- Name and identification number of notified laboratory, if relevant not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue
- 6. Declared performances

Essential characteristics	Performance	Harmonised technical specification	
Reaction to fire	A1		
Release of dangerous substance, for:			
- Cadmium	NPD		
- Lead	NPD		
Bond strength/adhesion, for:		BS EN 14411:2012	
Cementitious adhesive, type C1	>0,5 N/mm²		
Durability for:			
- internal use:	Pass		

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager)

Name and function

Onda, 01-01-2021

Place and date of issue

TAU CERAMICA SOLUTIONS, Z.L.U.
CACTUATA.
COMO THAT TOUR IN TO SPAIN





- Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption 0,5%< E_b ≤ 3%
- 2. Intended use(s)

For internal floorings

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

- Name and identification number of notified laboratory, if relevant not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue
- 6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 100 N	BS EN 14411:2012
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue

Signature

TAU CERAMICA SOLUTIONS, S.L.U. CIF B-12908112

Colle Del Toll, nº 18 12200 ONDA (CASTELLÓN) SPAIN





- Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with low water absorption E_b ≤0,5 %
- 2. Intended use(s)

For internal and external, floorings and wall finishes

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

- 4. System(s) of assessment and verification of constancy of performance (AVCP)

 Systems 4
- Name and identification number of notified laboratory, if relevant not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _F UA1	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 300 N	
Slipperiness	NPD	
Tactility	NPD	BS EN 14411:2012
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	> 1 N/mm ²	
Thermal shock resistance	Pass	
Durability for:		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021 Place and date of issue Signature

TAU CERAMICA
SOLUTIONS, S.L.U.
CIF B/12956112
Calle Del Toll/nº 18
12200 ONDA (CASTELLON) SPAIN





- Unique identification code of the product type
 Type, batch or serial number or any other element allowing identification of the product
 Dry-pressed ceramic tiles, with water absorption 3%< E_b ≤ 6%
- 2. Intended use(s)

For internal floorings

3. Name or registered trade mark, and contact address of the manufacturer

TAU CERAMICA SOLUTIONS, S.L.U.

Carrer del Toll, 18 // 12200 Onda (Castellón) SPAIN

4. System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

- Name and identification number of notified laboratory, if relevant not applicable
 Task(s) carried out
 AVCP system
 Document issued and date of issue
- 6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for:		
- Cadmium	NPD	
- Lead	NPD	
Breaking strength	> 1 000 N	BS EN 14411:2012
Slipperiness	NPD	
Tactility	NPD	
Durability for:		
- internal use:	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Mariano Sebastiá (Manager) Name and function

Onda, 01-01-2021

Place and date of issue

Signature

Caramica CIF B-12958112 Calle Del Toll, nº 18 12200 ONDA (CASTELLON) SPAIN